

PR16 Series Powered Rake

Specifications & Capacities				
Model Nos.		PR1660	PR1672	PR1690
Tractor horsepower range	hp (kW)	25-60 (18.6-44.7)	25-60 (18.6-44.7)	35-75 (26.1-55.9)
Non-angled working width	inch (m)	60 (1.52)	72 (1.83)	90 (2.29)
Weight	lbs (kg)	980 (444.5)	1000 (453.6)	1150 (521.6)
Hitch		Cat. I		Cat. I and II
Quick hitch		Fits Land Pride QH15 Cat. I Quick Hitch		
Gearbox		540 rpm, Ball Bearings, Cast Iron Housing, Drain Plug		
Gearbox oil capacity and lubrication type	pints (L)	SAE 90 Weight Gear Lube - 1 1/2 (.71) empty (Add gear lube until it escapes from lower plug hole.)		
Primary driveline		Cat. 3 Heavy-Duty		
Secondary driveline		Cat. 3 with Slip-Clutch		
Material control deflector	inch (mm)	1/2" X 5" (13 x 127) Urethane		
Spiked roller	inch (mm)	9 3/8 (238) Dia. with 3/4 (19) x 1 1/2 (38) Carbide Tipped Studs		
Roller end bearings		Ball Bearing		
Drive chain		#50 Double Roller Chain		
Angle adjustment		15 degrees left or right - Hydraulic or manual		
Angle cylinder		2" x 8"		
Side plates		Standard, Removable with Storage Rack		
Gauge wheels / Depth control		13" x 6.5"	16.5" x 6.5"	16.5" x 6.5"
		Air Tires with Sealant and 3/4" Roller Bearings and Spacer Height Adjustment		
Skid shoes		Replaceable		
Chaincase				
Lubrication type		Shell Gadus S2 V2200 00 flowable grease or equivalent		
Lubrication capacity	oz (L)	40 oz (1.18L)		

36785

